



Platinum Drive

PREMIUM DRIVEWAY CONCRETE

Platinum Drive from Wille Brothers

-  Contractors who want to offer a Premium Driveway Product to their customers.
-  COD's and Homeowners looking for a Better Driveway mix.
-  Contractors who are looking for fewer call backs from pop outs, scaling and unsightly shrinkage cracks.
-  Contractors who are looking for a driveway mix with better workability and finishability

Platinum Drive Specifications

Specifications:

Strength:	4500 Psi
W/C Ratio:	.44
Slump:	5 +/-1
Air:	6 +/- 1.5%
Fiber:	Grace Mono Finishing Fibers

Internal Sealer Included

Specifications exceed the requirement of the New ACI 318 code

Platinum Drive Benefits

- ▶ Avoids extra time and labor cost of external sealer
- ▶ Built-in resistance to cracking cost less than wire mesh, no labor
- ▶ Resists moisture and chemicals from day one
- ▶ Superior strength 4500 PSI as recommended by ACI 318
- ▶ Improved Durability for longer service life
- ▶ Designed at a 5" slump for easier placement and finish
- ▶ Cost savings vs 61D + Fiber + external sealer + labor

Internal Sealer Benefits

- ▶ Reduced penetration of water and other liquids
- ▶ Improved freeze-thaw durability
- ▶ No need to seal concrete after 28 days
 - ▶ Plant added integral sealer from day one
 - ▶ Sealing after one year is recommended
- ▶ Significantly reduces efflorescence
- ▶ Improves color vibrancy in colored concrete

GRACE MICROFIBER FDS

- ▶ Synthetic fiber for concrete 100% virgin polypropylene
- ▶ Reduces plastic shrinkage cracking by 90%
- ▶ Over 50 million individual fibers per cubic yard
- ▶ Super fine fibers improve finishing vs other fiber
- ▶ Grace Microfiber may be used as an alternative to welded wire fabric
- ▶ Automated FDS dispensing system assures fiber dosage and improves dispersion of fibers into concrete